



Flow Wall Hung Pan - Concealed Cistern

PRODUCT CODES

WHITE:	XTFLS08A	FLOW-WALL-HUNG-PAN (INCL CONCEALED CISTERN)
SEAT:	STCO4B08A	CONCEPT-SLIMLINE-SEAT

CONCEALED CISTERN & WALL HUNG

WEIGHT OF PAN:	27.5 kg
PAN WIDTH:	375 mm
PAN HEIGHT:	335 mm
INSTALLED MAX LENGTH:	420 mm
HEIGHT FROM GROUND:	85 mm

The Flow Wall Hung Pan is a pan for the concealed cistern.

FLOW WALL HUNG PAN INSTALLATION GUIDE:

- 1 - Please read the installation guide of the concealed cistern provided by the supplier. Make sure that the concealed cistern outlet pipe is at the same height of the pans inlet pipe.
- 2 - Use template supplied with box, to mark the exact attachment configuration. Centre of the outlet 232mm from floor, 330mm for the anchor bolts from the floor, and 380mm from the floor to the inlet water supply.
- 3 - The anchoring bolts need to be protruding from the wall by 40mm. Attach bullets to bolts to protrude by a total of 90mm from the wall with the bullet slots facing outwards to the sides.
- 4 - The water inlet needs to be 61mm protruded from the wall to reach the inlet pipe on the pan. The outlet is 16mm from the wall into the pan.
- 5 - Fit Flow pan to wall, align the back of the pan with the anchoring bolts and outlet, tighten firmly through the side holes with an allen-key, and then close side holes with plastic plug inserts.
- 6 - Attach the slimline seat to the pan.

AVAILABLE COLOURS:

